	1 2		3	4	5	6	7	8
Γ	,	I	I					
A								
								>
								0
								0
В								Ň
								C
	⊸ 1.37	78" ———						L
	0.039″ – (35m (1mm) – 20	im)						
		38" 0.295"						2
с	(27m							
	FRONT S							
								č
								-
	-							
								F
								Z
D		0.709"		984″	_ _			E
		(18mm)	(20)	-mm) (25mm)				
			(18mm) (25mm) (25mm)					
		<u> </u>						NO
		<u> </u>			$ \longrightarrow $			C C
		\rightarrow	Î					t s
-		0.248″ - (6.3mm))					
E		× · · · ·	BASE PERFORATION					
				—				
							Note:	
1. No sharp edges. 2. RoHS:The manufacturers must ensur and product components comply of the RoHS Regulations. 3. Previous part no. :								ers must ensure that their products
							and product compon of the RoHS Regulatio	ents comply with the requirements
Ļ								
	PCW Microsystems Inc	PROJECT NO.	66777 DOD DINDAIL 0	DRAWN	Kevin	MATERIAL	SPCC 2.0t	
F	PCW Microsystems Inc A leading developer of industrial rackmount products		RCB-DINRAIL-2 RCB-DINRAIL-2	APPV'D		FINISH	zink	TOLERANCES: ±0.15
	TEL:(516)997-5050 FAX:(516)997-5784	PART NO.	Din Rail	DATE	12/19/2013 V 1.2		1:1	SHEET 1 OF 1 UNIT:mm A3
L	©2012 PCW Microsystems Inc			REVISION	V 1.2	PROJECTION	Third Angle	UNIT:mm A3